

ONO (ALLROUND)

The **ONO Allround** offers maximum flexibility in **applications** such as **plant logistics, campus and facility management**. The ONO Allround can not only be used on **closed factory premises or campuses**, but can also be ridden **regularly in road traffic** - without a **driving license**, on the **bike infrastructure**.

With a **generous loading area of 170 x 82 cm**, an **anti-slip floor** and 6 lashing eyes for safe load securing, **various load carriers**, such as **Euro pallets (EPAL)** with stacking frames, **cage or big boxes** can be transported without any problems.

The **ONO Allround** transports loads of **up to 280 kg** (including the load carrier's own weight) and enables easy loading and unloading, **even with a forklift or via loading ramps**.

An **AES Superpack battery** enables a range of **up to 25 km**, and charging is effortless via a **conventional Schuko socket**.

Legal classification	Bicycle (Pedelec)
Dimensions	H: 205 cm W: 112,5 cm L: 340 cm
Vehicle Weight	220 kg (Empty)
Safeguard	Automatic locking mechanism
Vehicle Access	RFID-Chip
Power Source	1,400 Wh swappable and rechargeable batteries Standard range: 1 battery up to 25 km Optional 2nd battery (to take along in passive holder)
Engine	2 wheel hub motors with 113 Nm torque
Power	2 x 125 Watt nominal power output
Pedal-Assisted Speed	Up to 25 km/h
Pedal-Free Throttle	Up to 6 km/h
Max. Payload	280 kg (including tare weight of the load carrier)
Loading area	Various load carriers such as Euro pallets (EPAL) with stacking frames , cage or big boxes
Features	Loading area with anti-slip floor, 6 lashing eyes for load securing

